



MOWER SPECIFICATIONS

CZT ELITE MODELS



Cutting Width	4800/48"; 5400/54"; 6000/60"	4800/48"; 5400/54"; 6000/60"
Cutting Height	1.5"–4" with Deck Height Control System	1.5"–4" with Deck Height Control System
Blades	4800/1/4" x 2 1/2" x 16 1/2" , High Lift, Heat Treated 5400/1/4" x 2 1/2" x 18 1/2" , High Lift, Heat Treated 6000/1/4" x 2 1/2" x 20 1/2" , High Lift, Heat Treated	4800/1/4" x 2 1/2" x 16 1/2" , High Lift, Heat Treated 5400/1/4" x 2 1/2" x 18 3/4" , High Lift, Heat Treated 6000/1/4" x 2 1/2" x 20 1/2" , High Lift, Heat Treated
Lift and Height Adjustment	Instant Lift Electronic Actuator	Instant Lift Electronic Actuator
Blade Belt	Single V-Belt Spring Tension	Single V-Belt Spring Tension
Anti-Scalp Rollers	4800/4 Total (2 On Front, 2 In Rear) 5400/4 Total (2 Front, 2 Rear)/ 6000/6 Total (4 Front, 2 Rear)	4800/4 Total (2 On Front, 2 In Rear) 5400/4 Total (2 Front, 2 Rear)/ 6000/6 Total (4 Front, 2 Rear)
Deck Flotation	Floats on 2 Chains & 2 Front Leveling Arms	Floats on 2 Chains & 2 Front Leveling Arms
Deck Thickness	3/16" Thick Solid Steel	3/16" Thick Solid Steel
ENGINE		
Gross Horsepower	810cc Briggs Commercial Cyclonic	747cc Air-Cooled Kohler Confidant
Cylinders	90 Degree V-Twin	V-Twin
Displacement	810 cc	747 cc
Maximum Torque	42 ft. lbs. @ 2400 RPM	42.4 ft. lbs. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	11 Gallons	11 Gallons
Fuel Filter	Replaceable Automotive Type	Replaceable Automotive Type
Cooling System	Air-Cooled	Air-Cooled
Ignition	Electronic	Electronic
Starter	12 Volt	12 Volt
Charging System	20 amp	20 amp
DRIVE SYSTEM		
Transmission	Heavy-Duty Dual Integrated Hydrostatic Transaxle	Heavy-Duty Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Commercial Grade Gear Reduction	Integrated with Commercial Grade Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Axle	25 Micron, Replaceable Spin-On Type, 1 Per Axle
Pumps (2)	12 cc Pump and Motor Integrated in one unit	12 cc Pump and Motor Integrated in one unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit	7" Cooling Fan per Unit
Weight	4800/862 lbs; 5400/871 lbs; 6000/925 lbs.	4800/862 lbs; 5400/871 lbs; 6000/925 lbs.
Overall Height	49"	49"
Overall Width	4800/49 1/2"; 5400/55 1/2"; 6000/61 1/2"	4800/49 1/2"; 5400/55 1/2"; 6000/61 1/2"
Overall Length	75"	75"
Tire to Tire Width	46 1/2"	46 1/2"
Tires—Front	13 x 6.5–6 Smooth Tread	13 x 6.5–6 Smooth Tread
Tires—Rear	23 x 10.5–12 Turf Tread	23 x 10.5–12 Turf Tread
Steering	Dual Lever Steering, Independent Control	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 10 mph	Up to 10 mph
Parking Brake	Internal Parking Brake	Internal Parking Brake

ANOTHER MODEL ON NEXT PAGE

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2015. Bad Boy, Inc., All Rights Reserved.



MOWER SPECIFICATIONS

CZT ELITE MODELS

 **726cc**

Cutting Width	4800/48"; 5400/54"; 6000/60"
Cutting Height	1.5"–4" with Deck Height Control System
Blades	4800/1/4" x 2 1/2" x 16 1/2", High Lift, Heat Treated 5400/1/4" x 2 1/2" x 18 3/4", High Lift, Heat Treated 6000/1/4" x 2 1/2" x 20 1/2", High Lift, Heat Treated
Lift and Height Adjustment	Instant Lift Electronic Actuator
Blade Belt	Single V-Belt Spring Tension
Anti-Scalp Rollers	4800/4 Total (2 On Front, 2 In Rear) 5400/4 Total (2 Front, 2 Rear)/6000/6 Total (4 Front, 2 Rear)
Deck Flotation	Floats on 2 Chains & 2 Front Leveling Arms
Deck Thickness	3/16" Thick Solid Steel
ENGINE	
Gross Horsepower	726 Air-Cooled Kawasaki FS
Cylinders	V-Twin
Displacement	726 cc
Maximum Torque	40 ft. lbs. @ 2600 RPM
Fuel Requirement	Unleaded Gasoline (87 Octane or higher)
Fuel Capacity	11 Gallons
Fuel Filter	Replaceable Automotive Type
Cooling System	Air-Cooled
Ignition	Electronic
Starter	12 Volt
Charging System	20 amp
DRIVE SYSTEM	
Transmission	Heavy-Duty Dual Integrated Hydrostatic Transaxle
Pump Drive	Integrated Axial Piston Pump & Motor w/Gear Reduction
Wheel Drive	Integrated with Commercial Grade Gear Reduction
Hydrostatic System Oil	20W50 Motor Oil
Hydraulic Filter	25 Micron, Replaceable Spin-On Type, 1 Per Axle
Pumps (2)	12 cc Pump and Motor Integrated in one unit
Hydraulic Coolers (2)	7" Cooling Fan per Unit
Weight	4800/862 lbs; 5400/871 lbs; 6000/925 lbs.
Overall Height	49"
Overall Width	4800/49 1/2"; 5400/55 1/2"; 6000/61 1/2"
Overall Length	75"
Tire to Tire Width	46 1/2"
Tires—Front	13 x 6.5–6 Smooth Tread
Tires—Rear	23 x 10.5–12 Turf Tread
Steering	Dual Lever Steering, Independent Control
Turning Radius	Zero Degree, Turns Within Unit Length
Ground Speed (forward)	Up to 10 mph
Parking Brake	Internal Parking Brake

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2015. Bad Boy, Inc., All Rights Reserved.