



MOWER SPECIFICATIONS

MZ MODELS

KOHLER 725cc



540cc

| | | |
|-----------------------------------|---|---|
| Cutting Width | 42" | 42" |
| Cutting Height | 1"–4" with Deck Height Control System | 1"–4" with Deck Height Control System |
| Blades | 7/32" x 2 1/2" x 14 1/2", High Lift, Heat Treated | 7/32" x 2 1/2" x 14 1/2", High Lift, Heat Treated |
| Lift and Height Adjustment | Foot-Assist Lift | Foot-Assist Lift |
| Blade Belt | Single V-Belt Spring Tension | Single V-Belt Spring Tension |
| Anti-Scalp Rollers | 2 Total (2 Front) | 2 Total (2 Front) |
| Deck Flotation | Floats on 3 Leveling Linkages Along with 2 Anti-Sway Bars | Floats on 3 Leveling Linkages Along with 2 Anti-Sway Bars |
| Deck Thickness | 1/8" Thick Solid Steel | 1/8" Thick Solid Steel |
| ENGINE | | |
| Gross Horsepower | 726cc Air-Cooled Kawasaki FR | 540cc Air-Cooled Briggs & Stratton |
| Cylinders | 90 Degree V-Twin | Single Cylinder |
| Displacement | 726 cc | 540 cc |
| Maximum Torque | 40 ft Lbs @ 2600 RPM | 28 ft. lbs. @ 2600 RPM |
| Fuel Requirement | Unleaded Gasoline (87 Octane or higher) | Unleaded Gasoline (87 Octane or higher) |
| Fuel Capacity | 2.5 Gallons | 2.5 Gallons |
| Fuel Filter | Replaceable Automotive Type | Replaceable Automotive Type |
| Cooling System | Air-Cooled | Air-Cooled |
| Ignition | Electronic | Electronic |
| Starter | 12 Volt | 12 Volt |
| Charging System | 16 amp | 16 amp |
| DRIVE SYSTEM | | |
| Transmission | Dual Integrated Hydrostatic Transaxle | Dual Integrated Hydrostatic Transaxle |
| Pump Drive | Integrated Axial Piston Pump & Motor w/Gear Reduction | Integrated Axial Piston Pump & Motor w/Gear Reduction |
| Wheel Drive | Integrated with Gear Reduction | Integrated with Gear Reduction |
| Hydrostatic System Oil | 20W50 Motor Oil | 20W50 Motor Oil |
| Hydraulic Filter | — | — |
| Pumps (2) | EZT Integrated Unit | EZT Integrated Unit |
| Hydraulic Coolers (2) | 7" Cooling Fan per Unit | 7" Cooling Fan per Unit |
| Weight | 585 lbs | 585 lbs. |
| Overall Height | 42" | 42" |
| Overall Width | 42" | 42" |
| Overall Length | 67 3/4" | 67 3/4" |
| Tire to Tire Width | 41" | 41" |
| Tires—Front | 11 x 6.0-5 Smooth Tread | 11 x 6.0-5 Smooth Tread |
| Tires—Rear | 18 x 8.5-8 Turf Tread | 18 x 8.5-8 Turf Tread |
| Steering | Dual Lever Steering, Independent Control | Dual Lever Steering, Independent Control |
| Turning Radius | Zero Degree, Turns Within Unit Length | Zero Degree, Turns Within Unit Length |
| Ground Speed (forward) | Up to 6 mph | Up to 6 mph |
| Parking Brake | External Cogg Brake | External Cogg Brake |

SPECIFICATIONS ARE SUBJECT TO CHANGE.

We're constantly improving our products! For the latest videos, specifications, model improvements and information, please see us at www.badboymowers.com. Not responsible for typographical errors. ©2015. Bad Boy, Inc., All Rights Reserved.